

## SiwoPUD<sup>®</sup> - 8051F

**Characteristics:** Aqueous, aliphatic polyurethane dispersion based on polyether.

**Supplied as:** 35% in water

<b>Physical characteristics:</b>	Appearance	Translucence
	Non-volatile constituent	35 ±1 %
	PH value	7.5 - 9.5
	Viscosity	≤200 mPa s
	Mean particle size	≤100 nm
	NMP, NEP, DMAC	Free
	Glass transition temperature Tg	-35°C
	Elongation	1000-1100%
	Tensile strength	33.1 Mpa
	100% Modulus	1.9 Mpa
	Shear stability	good
	Yellowing resistance	non- yellowing

**Storage:** The dispersion should be stored in a frost-free place in tightly sealed containers. It contains no preservative.

**Application:** The film is soft, with excellent resilience, excellent alkali resistance and water fastness, good folding resistance at low temperature and high peel strength. It can be used for fabric printing coating, synthetic leather, etc.

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or suitability of any products for their own purposes. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such is free of patent infringement and are not recommendations to infringe on any patent.