

SiwoPUD-®1109

Characteristics: Cationic, aqueous, aliphatic polyurethane dispersion based on polyether.

Supplied as: 30% in water

Physical characteristics: Appearance Translucence

Non-volatile constituent 30 ± 1 %IonicityCationicPH value3.5- 5.5Viscosity ≤ 50 mPa sMean particle size ≤ 100 nmOrganic solvent4%

Glass transition temperation Tg

Elongation

Tensile strength

Elasticity modulus (100%)

Shear stability

Glass transition temperation Tg

-30°C

800-900%

5.03Mpa

0.55Mpa

good

Yellowing resistance non-yellowing

Storage: The dispersion should be stored in a frost-free place in tightly sealed containers.

It contains no preservative.

Application: The film is soft, mainly used in fabric processing and leather primer.

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or suitability of any products for their own purposes. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such is free of patent infringement and are not recommendations to infringe on any patent.

Contact: Brian Wei, SIWO US Inc, Duluth, GA. Tel: +1 859-333-9856/+86 19916703357, brianwei@siwo-us.com www.siwo-us.com