

SiwoPUD-®EC-600

Characteristics: Hydrophilic, aliphatic polyisocyanate.

Supplied as: 100%

Physical characteristics: Appearance Transparent

Non-volatile constituent(%) 100

IonicityNon-ionicNCO content $21.0\pm1\%$

Viscosity (mPa s) 1000-3000

Density(d420) 1.07

Monomeric diisocyanate content $\leq 0.2\%$

Storage: The crosslinker should be stored in tightly sealed containers, protected

against frost and away from direct sunlight.

Application: The crosslinker can be thinned or dispersed in water, and mainly

crosslinks the waterbased resins at room temperature (or high

temperature). It has lower viscosity, and is especifically for

water-based adhesives and water-based printing paste, etc.

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or suitability of any products for their own purposes. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such is free of patent infringement and are not recommendations to infringe on any patent.

Contact: Brian Wei, SIWO US Inc, Duluth, GA. Tel: +1 859-333-9856/+86 19916703357, brianwei@siwo-us.com www.siwo-us.com