

SiwoPUD® -352F

Characteristics: Aqueous, aliphatic polyurethane dispersion based on polyether and polyester.

Supplied as: 35% in water

Physical characteristics:	Appearance	Translucence
	Non-volatile constituent	35±1 %
	PH value	7.5 - 9.5
	Viscosity	≤300mPa s
	Mean particle size	≤100 nm
	Glass transition temperature Tg	-25°C
	NMP, NEP, DMAC	Free
	Elongation	300-400%
	Tensile strength	19.3Mpa
	100%Modulus	8.9Mpa
	Shear stability	good
	Dry	Fast
	Yellowing resistance	non- yellowing

Storage: The dispersion should be stored in a frost-free place in tightly sealed containers. It contains no preservative.

Application: Its coating film exhibits medium hardness. It exhibits high gloss, excellent water resistance, excellent abrasion resistance, and good NaOH and hydrolysis resistance. It can be used in rubber, leather, and textile coatings.

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or suitability of any products for their own purposes. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such is free of patent infringement and are not recommendations to infringe on any patent.