

SiwoPUD[®]-U-5702

Characteristics: It is an aqueous anionic polyurethane dispersion of a high molecular weight. It is a raw material for formulation of heat-activated adhesives.

Supplied as: 50% in water

Physical characteristics:	Appearance	Milky white
	Non-volatile constituent	50±1 %
	PH value	6.5 – 8.5
	Viscosity	≤ 300 mPa s
	Density(d ₄ ²⁰)	1.05
	NMP, NEP, DMAC etc.	Free
	Minimum film-forming temperature	5°C
	Minimum activation temperature	100-110°C
	Elongation	1350%
	Tensile strength	21.2 Mpa
	100%Modulus	1.6 Mpa
	Yellowing resistance	non- yellowing

Storage: The dispersion should be stored in a frost-free place in tightly sealed containers. It contains no preservative.

Application: The film has excellent elasticity, high strength and heat-activated performance at a high temperature. Suitable for fabric coating, thermal transfer, plastic and elastomer substrate bonding, bonding automotive interior. Its properties can be increased by the addition of 2-5% by weight of a water-dispersible polyisocyanate.

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or suitability of any products for their own purposes. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such is free of patent infringement and are not recommendations to infringe on any patent.