Answers for waterborne coatings & adhesives

思沃®化学
SiwoChem

SiwoPUD®-6993S

Characteristics: Small-particle-size waterborne polyurethane dispersion based on polycarbonate.

Supplied as: 32% in water

Physical characteristics:

Appearance	Translucence-white
Non-volatile constituent	31-33 %
PH value	7.0 - 9.5
Viscosity	≤200mPa·s
NMP, NEP, DMAC	Free
Elongation	1000-1100%
Tensile strength	19.1Mpa
100%Modulus	1.1Mpa
Dry	Fast
Shear stability	Good
Yellowing resistance	Non- yellowing

Storage: The dispersion should be stored in a frost-free place in tightly sealed containers. It contains no preservative.

Application: The dispersion has a small particle size. The coating film is clear and transparent with a soft feel. It exhibits excellent adhesion and dry/wet rub resistance on leather, as well as excellent flex resistance and low-temperature resistance. It is recommended for digital printing ink applications .

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or suitability of any products for their own purposes. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such is free of patent infringement and are not recommendations to infringe on any patent.

Shanghai Sisheng Polymer Materials Co., Ltd. Address: No.155 Ping Ye Road, Caojing Town, Jinshan District, Shanghai 201507, P R China.
Contact: Brian Wei Tel +1 859-333-9856, Na Da Tel +86 15166916376, www.siwo-us.com.